

LSL SERIES

40W 80W 120W 160W 200W
240W



LED STREETLIGHT SERIES



The innovative LSL series offers a stylish aesthetic and high performance LED chip combined with a special heat sink design. The LSL is fully IP66 rated and has superb dust and dirt resistance allowing superior heat dissipation resulting in a lifetime exceeding 50,000 hours.

MAIN FEATURES

- High efficiency rating
- Light Harvest Sensor*
- 1-10V/PWM/Resistance dimming*
- SAA Approved
- EEIS (ACT) Approved
- 5 Year Warranty
- Available with different reflectors
- 80°, 100°, 120° Degree beam angle
- Different colour housings available

*Available upon request

APPLICATIONS

- Street
- Carpark

SPECIFICATIONS

CCT	3000k-6500k
Chip Type	SMD (Philips Lumileds)
Dimmable	No
Ingress Protection	IP66
Sensor	Yes
IPART Approved	Yes





LSL SERIES

LED STREETLIGHT SERIES 40W 80W 120W 160W 200W 240W













PRODUCT PARAMETERS

Part Number	Weight	Wattage	CRI	Luminous Flux	Light Efficiency	Input Voltage	Powerfactor	Driver
LSL-40W-WOLFE	5.5kg	40W	>75	4400lm	110lm/w	240v	>0.95	Integrated
LSL-80W-WOLFE	7.5kg	80W	>75	8800lm	110lm/w	240v	>0.95	Integrated
LSL-120W-WOLFE	8.4kg	120W	>75	13200lm	110lm/w	240v	>0.95	Integrated
LSL-160W-WOLFE	9.7kg	160W	>75	17600lm	110lm/w	240v	>0.95	Integrated
LSL-200W-WOLFE	10.8kg	200W	>75	22000lm	110lm/w	240v	>0.95	Integrated
LSL-240W-WOLFE	11.6kg	240W	>75	26400lm	110lm/w	240v	>0.95	Integrated

PHOTOMETRICS



DIMENSIONS (mm)



AUTHORISED REPRESENTATIVE

CARBON REDUCTION INSTITUTE



Unit 33, 20-28 Maddox Street
Alexandria, NSW 2015 Australia
ABN 47 622 447 349